

Tender 1

AB Inflatable, Profile (aluminium) A 11, Commercial Series

(new 2014)



The Profile A series aluminium RIB, by AB Inflatables is designed for the professional commercial organization which requires a heavy duty aluminium RIB. The Profile A series RIB is popular with fire and rescue organizations in the USA as well as with government organizations.

The Profile A, RIB series is designed to be lightweight and capable of being used with relatively small horsepower motors to make the RIB easily transportable and more manoeuvrable, when having to manhandle the RIBs in operational circumstances.

The build of the A series is robust to make it less vulnerable which is evident in the tough aluminium hull together with heavy duty hypalon tubes which are made of heavy duty 1670 hypalon(military grade) and heavy duty rubstrake. The tough heavy duty handles facilitate manoeuvring and carrying over rough terrain. All in all this is one tough inflatable boat.

The Profile A series aluminium RIB comes with a self drain system





Modell ⁽¹⁾	a. E30DPL b. E30DEL c. E30DTL d. E30DTEL	e. E30DRL f. E30DR g. E30DRS h. E30DRSL	i. E30TESL j. E30DPSL k. E30DTSL
Schaftlänge mm (inch) / Farbe	a. / b. / c. / d. / e. 508 (20") Blau h. / i. / j. / k. 508 (20") Weiß f. 381 (15") Blau g. 381 (15") Weiß		
Gewicht kg (lbs)	a./j. 80 (177) / b. 71 (156) / c./k. 83 (183) / d./i. 73 (162) / e./h. 68 (150) / f./g. 66 (146)		
Motortyp	Zweizylinder-Reihenmotor E-TEC Direkteinspritzung		
Bohrung x Hub mm (in)	76 x 64 (2.992 x 2.500)		
Hubraum ccm (cu in)	577 (35.2)		
Zündsystem	IDI Fast Rise Induktiv-Zündsystem		
Start	a./b./ c. /d./i./j./k. Elektrisch & Handstart e. / f. Handstart		
Trimmung	a. / c. / j. / k. Power Trim & Tilt b. / d. / e. / f. / g. / h. / i. Manuelle Kippvorrichtung		
Propellerwelle (kw)*	22 kw (30PS) @ 5500 RPM		
Betriebsbereich bei Vollgas	5700-6100 RPM		
Untersetzungsverhältnis	2.15:1		
Kraftstoffzufuhr	E-TEC Kraftstoffdirekteinspritzung mit geschichteter Einspritzung im niedrigen Drehzahlbereich		
Lichtmaschine	Rechnergesteuerte, variable Stromspannung, 56 Amp** / 750 Watt Ausgangsleistung mit Regler		
Kühlung	Druck- und temperaturgesteuerte Wasserkühlung		
Steuerung	a. / b. / j. Ferngesteuert (Pinne optional) c. / d. / e. / f. / g. / h. / i. / k. Pinne (Ferngesteuert optional)		
Herstellergarantie	Auf 5 Jahre erweitertes (Standard 3 + 2) beschränktes Garantieprogramm***		
Erfüllte Abgasnorm	EPA 2010 CARB 3 STAR EU		

(1) Ausgewählte Modelle sind offiziell für den Bodensee registriert und dürfen dort gefahren werden.

* Leistungsangaben gemessen an der Propellerwelle in Anlehnung an NMMA nach ICOMIA Standards 28/83.

** Der Strom von 56 A wird bei 13.5 V berechnet. Der für das Laden der Batterie vorgesehene Nettoausgangsstrom beträgt 15 A.

*** Beschränkt auf Evinrude MY10 und neuere Motoren, nur für Freizeitwecke. 65 PS und 90 PS Arbeitsmotoren ausgeschlossen. Es gelten spezielle Bedingungen. 5 Jahre oder 750 Stunden, je nachdem, was zuerst eintritt. Bitte wenden Sie sich an Ihren teilnehmenden BRP Vertragshändler, besuchen Sie brp.com oder lesen Sie unsere Evinrude Broschüre für alle Einzelheiten.

©2014 Bombardier Recreational Products Inc. Alle Rechte vorbehalten.

®™ und das BRP Logo sind Markenzeichen der Bombardier Recreational Products Inc. oder ihrer Tochtergesellschaften.



Tender 2

Quick Inflatable, lightweight
(new 2015)



- Dimension 2,20m x 1,40m
- inflatable bottom
- only 32 kg weight

The tender can easily be lifted on board by hand, or with KEMMUNA's winches. The tender is stored on the roof of the pilothouse. It is ideal for 2 persons for short distances.

Torqueedo Travel 1003 electric outboard engine

Can do everything that a 3 HP petrol outboard can, plus it's environmentally friendlier, quieter, lighter and more convenient

- On-board computer with GPS-based calculation of remaining range
- Solar rechargeable – including during the voyage
- Can be easily dismantled for transport and space-saving storage
- A clean affair: no matter how or where you store your Travel, there's no risk of leakage or petrol smells
- Stepless forward/reverse drive
- Manual tilting device with grounding protection
- 4-step manual trim device
- Completely waterproof (IP 67)
- Tiller control
- Integrated battery with 530 Wh Li-Ion
- Total weight 14.4 - 15.5 kg
- Shaft length: long 75 cm

